

Finest ideas in Cooling and Retail Solutions...



 THE MIDDLEBY CORPORATION

...brought to India by Middleby Celfrost

Hard Top Chest Freezers from 100 ltrs to 850 ltrs.

Presenting world's finest range of convertible chest freezers/coolers to suit every need, in one, two and three lid variants



CF-100/110
CF-115**



CF-200/210/300/310
CF-215/335**



CF-350 DD



CF-400/460/560
CF-445/585**



CF-860

Half Freezer / Half Cooler



CFCC-300/400/500/
CFCC-335**

- Unique dual temperature design with separate freezing and cooling chamber
- 2 separate lids for easy access to either chamber

Special Application Freezers/Coolers



CF-60



CF-300 SS/430 SS

- Features:**
- Copper evaporator coils



CF-600 SS

- Features:**
- Complete SS construction inside and outside

Technical Specification

| Product/Model Specification | Hard Top Chest Freezers / Chillers | | | | | | | | | | | | | | | | SS Series | | | Half Freezer / Cooler | | | | | | |
|-----------------------------|------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------------------|-----------|----------|----------|-----------|-----|--|
| | CF 60 | CF 100 | CF 110 | CF 115 | CF 200 | CF 210 | CF 215 | CF 300 | CF 310 | CF 335 | CF 350 DD | CF 400 DD | CF 445 DD | CF 460 DD | CF 560 DD | CF 585 DD | CF 860 | CF 330 SS | CF 430 SS | CF 600 SS | CFCC 300 | CFCC 335 | CFCC 400 | CFCC 500 | | |
| Capacity (litres) | 60 | 100 | 105 | 100 | 230 | 210 | 230 | 330 | 320 | 330 | 330 | 380 | 423 | 425 | 525 | 520 | 850 | 290 | 390 | 577 | 136F+150C | 300 | 400 | 316F+155C | | |
| Dimension (inch) Width | 21 | 23 | 22 | 23 | 33 | 36 | 33 | 43 | 39 | 44 | 45 | 51 | 59 | 49 | 61 | 63 | 95 | 41 | 50 | 71 | 49 | 49 | 52 | 60 | | |
| Depth | 19 | 22 | 22 | 22 | 26 | 22 | 26 | 26 | 29 | 27 | 29 | 26 | 27 | 29 | 29 | 30 | 29 | 30 | 30 | 28 | 24 | 24 | 28 | 30 | | |
| Height | 24 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 34 | 33 | 33 | 34 | 34 | 33 | 35 | 33 | 33 | 37 | 36 | 36 | 37 | 36 | | |
| Temperature Range | -18°C ~ -24°C / 2°C ~ 8°C | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wheels | NA | Yes | Yes* | Yes | Yes | Yes* | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes* | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Lock | NA | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Refrigerant | R600a | R134a | R600a | R134a | R134a | R600a | R134a | R134a | R290 | R134a | R134a | R134a | R134a | R290 | R290 | R134a | R290 | R134a | R134a | R404a | R134a | R134a | R600a | R600a | | |
| Rated Load, Wattage | 80 | 110 | 70 | 100 | 170 | 70 | 125 | 220 | 160 | 295 | 160 | 185 | 295 | 240 | 275 | 350 | 295 | 155 | 170 | 295 | 150 | 195 | 160 | 200 | | |
| No. of Baskets | NA | 1 | 2 | 1 | 1 | 2 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | | |
| No. of Lids/Doors | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 2 | 2 | 3 | 1 | 1 | 2 | 2 | 2 | 2 | 2 | | |

Specifications, features and colours are subject to change without any notice, due to continuous product development.

*This height without wheels.

**White painted sheet inside

Glass Top Freezers



IKG-111



IKG-211/311/411



IKG-511/611



IKG-210C



IKG-310C/410C



Island Freezer



IL-450/550

Canopy optional & can be fixed on all flat/curved glass top freezers to make it a scooping cabinets

- Ultra low energy consumption
- Longer holding
- Fastest cooling
- Special design end to end basket

Technical Specification

| Product / Model Specification | Flate Glass Chest Freezers | | | | | | Curve Glass Chest Freezers | | | Island Showcase | | |
|-------------------------------|----------------------------|---------|---------|---------|---------|---------|----------------------------|----------|----------|-----------------|--------|----|
| | IKG-111 | IKG-211 | IKG-311 | IKG-411 | IKG-511 | IKG-611 | IKG-210C | IKG-310C | IKG-410C | IL-450 | IL-550 | |
| Capacity (litres) | 97 | 194 | 300 | 380 | 500 | 600 | 200 | 300 | 400 | 426 | 528 | |
| Dimension (inch) | Width | 24 | 37 | 40 | 48 | 56 | 65 | 30 | 41 | 48 | 70 | 77 |
| | Depth | 21 | 23 | 27 | 27 | 27 | 27 | 26 | 27 | 27 | 29 | 36 |
| Height | 33 | 33 | 32 | 32 | 32 | 32 | 33 | 32 | 32 | 34 | 39 | |
| Temperature Range | -18°C ~ -24°C | | | | | | | | | -18°C ~ -22°C | | |
| Wheels | Yes | Yes | Yes | Yes | Yes | Yes | Yes* | Yes* | Yes* | Yes | Yes | |
| Lock | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Refrigerant | R134a | R134a | R290 | R290 | R290 | R290 | R290 | R290 | R290 | R134a | R134a | |
| Rated Load, Wattage | 160 | 160 | 275 | 275 | 295 | 295 | 240 | 275 | 275 | 275 | 310 | |
| No. of Baskets | 1*+1 | 1*+1 | 2*+2 | 2*+2 | 2*+2 | 2*+2 | 1*+1 | 2*+2 | 2*+3 | 4 | 6 | |
| No. of Lids/Doors | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | |

Specifications, features and colours are subject to change without any notice, due to continuous product development.

*This height without wheels.

‡ QDI Baskets



Showcase Freezers



NFG-200*



NFG-450*



NFG-1000A*



NFG-1500*

Technical Specification

| Upright Showcase Freezers | Product / Model Specification | | | | | | | | |
|---------------------------|-------------------------------|------------------------|-------------------|--------|------|-------------|---------------------|-------------------------|--------------------|
| | Capacity (litres) | Dimension (WxDxH) inch | Temperature Range | Wheels | Lock | Refrigerant | Rated Load, Wattage | No. of Baskets/ Shelves | No. of Lids /Doors |
| NFG-200 | 211 | 24 x 28 x 39 | -18°C ~ -22°C* | Yes | Yes | R404a | 700 | 2 | 1 |
| NFG-450 | 450 | 27 x 28 x 78 | -18°C ~ -22°C* | Yes | Yes | R404a | 1000 | 5 | 1 |
| NFG-1000A | 1078 | 54 x 28 x 78 | -18°C ~ -22°C* | Yes | Yes | R404a | 1100 | 10 | 2 |
| NFG-1500 | 1657 | 81 x 28 x 78 | -18°C ~ -22°C* | Yes | Yes | R404a | 1300 | 4 x 3 | 3 |

* Suitable to work at ambient temperature 28°C

Complete range for retail solutions



IKG 60



FKG 20C/58C



NFG 58C



NFGC 49



TG 3



CBF 67



FSDCR 108/FSDHR 108



FSDC 58



Showcase Coolers



FKG-120



FKG-230



FKG-320/400



FKG-371



FKG-230/330/430



FKG-610



FKG-600 DD



FKG-1000S



FKG-1500

Technical Specification

| Product/Model Specification | Upright Showcase Coolers | | | | | | | | | | | |
|-----------------------------|--------------------------|---------|---------|---------|---------|---------|---------|---------|------------|-----------|----------|-------|
| | FKG-120 | FKG-230 | FKG-320 | FKG-330 | FKG-371 | FKG-400 | FKG-430 | FKG-610 | FKG-600 DD | FKG-1000S | FKG-1500 | |
| Capacity (litres) | 120 | 200 | 300 | 300 | 381 | 400 | 400 | 600 | 630 | 1030 | 1657 | |
| Dimension (inch) | Width | 22 | 20 | 21 | 22 | 23 | 24 | 25 | 28 | 36 | 47 | 81 |
| | Depth | 23 | 23 | 25 | 24 | 23 | 27 | 24 | 29 | 27 | 28 | 28 |
| | Height | 39 | 60 | 68 | 71 | 73 | 78 | 81 | 81 | 78 | 78 | 78 |
| Temperature Range | 2°C ~ 10°C | | | | | | | | | | | |
| Wheels | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Lock | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Refrigerant | R600a | R600a | R134a | R600a | R134a | R134a | R600a | R134a | R134a | R134a | R134a | R134a |
| Rated Load, Wattage | 170 | 190 | 195 | 200 | 350 | 240 | 250 | 390 | 350 | 550 | 800 | |
| No. of Shelves | 2 | 3 | 4 | 4 | 6 | 4 | 4 | 5 | 4+4 | 4+4 | 4+4+4 | |
| No. of Lids/Doors | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 3 | |

* Suitable to work at ambient temperature 28°C



HTS 1000 / 1200 / 1500



HTS 500



IL-450/550



HTS 380

Technical Specification

| Product/Model Specification | Freezers / Chillers | | | | | | | | | | | | Island Showcase | | Multideck Chillers | | | | | |
|-----------------------------|---------------------|--------------|--------|--------|-----------------------------|-------------|-----------------|---------|----------------|---------|-----------------|---------|-----------------|-------------|--------------------|-----------------|----------|----------|----------|----|
| | FSDHR 108 | FSDCR 108 | IKG 60 | TG 3 | CBF 67 | FSDC 58 | FKG 20C | FKG 58C | FKG 80C | NFGC 49 | NFG 42C | NFG 58C | IL-450 | IL-550 | HTS 380 | HTS 500 | HTS 1000 | HTS 1200 | HTS 1500 | |
| Capacity (litres) | 108 | 108 | 40 | 39 | 27 | 58 | 20 | 58 | 80 | 55 | 42 | 58 | 426 | 528 | 380 | 220 | 770 | 950 | 1125 | |
| Dimension (inch) | Width | 19 | 19 | 23 | 27 | 32 | 17 | 13 | 17 | 18 | 24 | 17 | 18 | 70 | 77 | 39 | 19 | 42 | 50 | 61 |
| | Depth | 19 | 19 | 21 | 28 | 26 | 16 | 14 | 18 | 19 | 21 | 19 | 19 | 29 | 36 | 35 | 24 | 30 | 30 | 30 |
| Height | 34 | 34 | 20 | 21 | 14 | 33 | 23 | 31 | 37 | 27 | 30 | 36 | 34 | 39 | 60 | 71 | 78 | 78 | 78 | |
| Temperature Range | 30°C ~ 90°C | 2°C ~ 10°C* | -18°C* | -18°C* | -18°C ~ -22°C / 2°C ~ 10°C* | 2°C ~ 10°C* | | | -18°C ~ -22°C* | | | | | 2°C ~ 10°C* | | | | | | |
| Wheels | Adjustable Feet | | NA | NA | Adjustable Feet | Legs | Adjustable Feet | | | Legs | Adjustable Feet | | Yes | Yes | Yes | Adjustable Feet | | | | |
| Lock | Optional | Optional | NA | NA | NA | Yes | Optional | | | Yes | Optional | | Yes | Yes | NA | NA | NA | NA | NA | |
| Refrigerant | NA | R600a | R134a | R134a | R600a | R600a | R600a | R600a | R600a | R290 | R134a | R134a | R134a | R134a | R290 | R404a | R404a | R404a | R404a | |
| Rated Load, Wattage | 1200 | 230 | | 170 | 140 | 180 | 82 | 82 | 94 | 100 | 130 | 150 | 275 | 310 | 1300 | 830 | 1100 | 1100 | 1650 | |
| No. of Baskets/Shelves | 4 (Rotating) | 4 (Rotating) | 1 | | 8*1/6 GN PAN | 2 | 1 | 2 | 3 | 2 | 3 | 3 | 4 | 6 | 3 | 3 | 4 | 4 | 4 | |
| No. of Lids/Doors | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | NA | NA | NA | NA | NA | |

* Suitable to work at ambient temperature 28°C

* Suitable to work at ambient temperature 32°C



Multideck Chiller

(Close door option available in Chiller & Freezer)

Display-cum Storage Coldroom

Cool, soothing
drops of water
collected for you,
by Middleby
Celfrost!

24 month
Compressor
Warranty*



S.Dlx.
20/20

S.Dlx.
20/40

S.Dlx.
40/80

S.Dlx.
60/120

S.Dlx.
150/150

S.Dlx.
200/400

Technical Specifications

| Model | S.Dlx. 20/20 | S.Dlx. 20/40 | S.Dlx. 40/40 | S.Dlx. 40/80 | S.Dlx. 60/120 | S.Dlx. 150/150 | S.Dlx. 200/400 |
|--|------------------------------|------------------|-----------------------------|------------------|------------------|------------------|---------------------|
| Cooling Capacity | 20 | 20 | 40 | 40 | 60 | 150 | 200 |
| At 10°C temperature drop (Ltr/hr) | 35 | 35 | 65 | 65 | 100 | 245 | 400 |
| Glasses/hr at rated condition (Ltr/hr) | 100 | 100 | 200 | 200 | 300 | 750 | 1000 |
| Storage Capacity (Ltr) | 20 | 40 | 40 | 80 | 120 | 150 | 400 |
| No. of Faucets - cold water | 1 | 1 | 1 | 2 | 2 | 2 | 4 |
| Faucets Material | Brass (Cr Plated) | | | | | | |
| Dimensions (mm) | 370 x 370 x 1000 | 370 x 370 x 1185 | 370 x 370 x 1185 | 590 x 490 x 1200 | 700 x 540 x 1160 | 700 x 540 x 1320 | 1160 x 700 x 1400 |
| Compressor / Make | Emerson 419 / LG-MA 53 | | Emerson 443, 444 / LG-MA 88 | | Emerson 461 | Emerson 513 | Emerson 513 / CR 22 |
| Compressor / Refrigerant | R-134a | R-134a | R-134a | R-134a / R-22 | R-22 | R-22 | R-22 |
| Power (Watts) | 390 | 390 | 450 | 450 | 775 | 1550 | 2000 |
| Net Weight (Kgs.) | 33 | 35 | 43 | 48 | 55 | 70 | 90 |
| Legs | Nylon | | | | | | |
| Water inlet hose pipe | Provided (Food Grade) | | | | | | |
| Drain Pipe | Provided | | | | | | |
| Over Flow Pipe | Provided | | | | | | |
| Motor Make | Micro / Marathon (GE Motors) | | | | | | |

Note:

- All Models are suitable for operation on 230V / 1Ph / 50Hz AC Supply.
- Specification and features are subject to change without notice, due to continuous product development.


THE MIDDLEBY CORPORATION


MIDDLEBY CELFROST

Middleby Celfrost Innovations (P) Ltd.

Corp. Office : Unit Nos. SF-713 – 716, 7th Floor, JMD Megapolis, Sohna Road, Sector 48, Gurgaon - 122 018, Haryana, India.

Tel. : +91 124 482 8500, Fax : +91 124 427 9663, E-mail : corp@middlebycelfrost.com, Web : www.middlebycelfrost.com

Toll Free Customer Service No.: 1800-102-1980 • service.india@middlebycelfrost.com

ONE PARTNER. ONE TEAM. MANY SOLUTIONS.



For sales related queries :-

Call: 89294 92780 • Email: sales@middlebycelfrost.com